Application No.: 10/538,072 Docket No.: R2184.0364/P364

## **AMENDMENTS TO THE CLAIMS**

1. (Original) An optical information recording method of an optical information recording and reproduction device that uses a semiconductor laser to record or reproduce data in an optical recording medium, said optical information recording method comprising a step of:

adjusting a calculated value of optimum recording power for recording data or an object value of recording power when data are being recorded, based on a detected value of an optical path difference of the optical recording medium.

2. (Original) The optical information recording method as claimed in claim 1, wherein

when calculating the optimum recording power before recording data in the optical recording medium, an optimum index indicating the optimum recording power is corrected with respect to a predetermined first index based on the detected value of the optical path difference of the optical recording medium, and the corrected optimum index is used as the calculated value of the optimum recording power, said predetermined first index being obtained by reproducing a trial write region that is recorded with recording power being varied stepwise.

3. (Original) The optical information recording method as claimed in claim 2, wherein

a value of the predetermined first index is an asymmetric value equaling a ratio of a difference between a maximum and a minimum of a direct current component of a reproduction signal from the trial write region to a sum of the maximum and the minimum.

4. (Original) The optical information recording method as claimed in claim 1, wherein

an object index indicating the optimum recording power is corrected and updated continually based on the detected value of the optical path difference of the optical recording medium with respect to a predetermined second index, and the corrected object index is used to correct the optimum recording power while recording, said predetermined second index being obtained from a detection signal associated with an amount of light reflected from the optical recording medium when data are being recorded in the optical recording medium.

5. (Currently Amended) The optical information recording method as claimed in claim 4, wherein

a value of the third second index is an average value of the detected signal associated with the amount of reflected light or a sample value of the amount of reflected light when forming a recording mark normalized by the recording power.

Application No.: 10/538,072 Docket No.: R2184.0364/P364

6. (Currently Amended) The optical information recording method as claimed in any one of claims claim 1 through 5, wherein

an initial value of the optical path difference of the optical recording medium is obtained by reading out information of the optical path difference of the optical recording medium or information of a distribution of the optical path difference of the optical recording medium from pre-format information to calculate a detected value of the optical path difference before the data are recorded or when the data are being recorded.

7. (Currently Amended) The optical information recording method as claimed in any one of claims claim 2 1 through 6, wherein

a change of the optical path difference is calculated from the amount of light reflected from the optical recording medium; and

the first index or the third second index is corrected by a conversion unit according to the change.

8. (Currently Amended) The optical information recording method as claimed in any one of claims claim 2 1 through 6, wherein

the first index or the third second index is corrected by using a detected value of a detection unit for detecting an elliptically polarized light beam component of the light reflected from the optical recording medium.

- 9. (Currently Amended) The optical information recording method as claimed in any one of claims claim 2 1 through 6, wherein the first index or the third second index is corrected by using a detected value of a temperature or a change of the temperature near the optical recording medium based on desired temperature dependence.
- 10. (Currently Amended) An optical disk used as an optical recording medium in an optical information recording and reproduction device, said optical disk being recorded with information by using the information recording method as claimed in any one of claims 1 through 9 claim 6, wherein

information indicating an optical path difference of a trial write region assigned to the optical disk or distribution information of the optical path difference of the optical disk in a radial direction is formed in advance as recording condition information or recording management information among pre-format information of the optical disk.

- 11. (Original) An optical information recording and reproduction device that uses the semiconductor laser to record or reproduce data in the optical recording medium by using the information recording method as claimed in any one of claims 1 through 9.
- 12. (Original) The optical information recording and reproduction device as claimed in claim 11, wherein the optical disk as claimed in claim 10 is used as the optical recording medium.

Application No.: 10/538,072 Docket No.: R2184.0364/P364

13. (New) The optical information recording method as claimed in claim 5, wherein

a change of the optical path difference is calculated from the amount of light reflected from the optical recording medium; and

the first index or the second index is corrected by a conversion unit according to the change.

14. (New) The optical information recording method as claimed in claim 5, wherein

the first index or the second index is corrected by using a detected value of a detection unit for detecting an elliptically polarized light beam component of the light reflected from the optical recording medium.

15. (New) The optical information recording method as claimed in claim 5, wherein the first index or the second index is corrected by using a detected value of a temperature or a change of the temperature near the optical recording medium based on desired temperature dependence.